

■ MODELS

	ABA 850	ABA 1100	ABA 1400
Max. Film Width Maks.Film Geniřliđi	750mm	1000mm	1200mm
Thickness of the Film Film Kalınlıđı	8-150 micron	8-150 micron	10-150 micron
Max. Output Capacity / Maks. Üretim Kapasitesi	90kg/h	120kg/h	220kg/h
EXTRUSION UNIT – EKSTRÜZYON ÜNİTESİ			
Main Motor Ana Motor	A: 15kW B: 22kW	A: 18.5kW B: 30kW	A: 45kW B: 55kW
Screw Diameter Vida Çapı	A: Ø45-B: Ø55	A: Ø50-B: Ø60	A: Ø70-B: Ø80
Screw & Barrel Material / Vida & Kovan Malzemesi	8550 Nitration Steel	8550 Nitration Steel	8550 Nitration Steel
Screw Ratio L/D Vida Orantısı	30/1	30/1	30/1
Barrel Air Cooling Fans Kovan Sođutma Fanları	A:3 x 0,18kW B:3 x 0,18kW	A:3 x 0,18kW B:3 x 0,25kW	A:4 x 0,25kW B:5 x 0,25kW
Type of Screen Changer Süzgeç Tipi	Manual Arm Type Manuel Kollu Tip	Manual Arm Type Manuel Kollu Tip	Manual Arm Type Manuel Kollu Tip
DIE UNIT – KAFA ÜNİTESİ			
Type of The Die Head Kafa Tipi	Fixed Head Sabit Kafa	Fixed Head Sabit Kafa	Fixed Head Sabit Kafa
Die Diameter Kafa Çapı	HDPE Ø 90	HDPE Ø 125	HDPE Ø 175mm
Air Blower Fan Balon Sođutma Fanı	4kW	5,5kW	15kW
HAUL-OFF UNIT – ÇEKİCİ ÜNİTESİ			
Type of The Tower Kule Tipi	Fixed Tower Sabit Kule	Fixed Tower Sabit Kule	Rotary Tower Döner Kule
Haul-Off Roller Dia. & Width Çekici Silindir Çapı & Geniřliđi	Ø165 mm-850	Ø165 mm-1100	Ø 230 mm-1400
Haul-Off Motor Çekici Silindir Motoru	1,1kW	1,5kW	3kW
Height of The Machine Kule Yüksekliđi	5m	5,5m	8,5m
WINDER UNIT – SARGI ÜNİTESİ			
Type of Winder Sargı Tipi	Manuel Winder Manuel Sargı	Manuel Winder Manuel Sargı	Automatic Winder Otomatik Sargı
Winder Roller Dia. & Width Sarcı Silindir Çapı & Geniřliđi	Ø 240 mm-850mm	Ø 240 mm-1100mm	Ø 380 mm-1400
Winder Roller Motor Sarcı Silindir Motoru	1,1kW	1,5kW	3kW
Max. Roll Diameter Maks. Bobin Çapı	Ø 750 mm	Ø 750 mm	Ø 800 mm



Shortcut to our
Plastic Processing
Technology

Plastik İşleme
Teknolojimize Kısa
Yoldan Ulaşın



**High Quality Film Production
with Mono Fixed Die,
Rotating Tower**

Mono Split Kafa,
Döner Kule İle Yüksek Kaliteli
Film Üretimi